

Septic System Pumping Record Hamilton, MA

1. System Location: _____
Address

2. System Owner: _____
Name Phone

3. Date of Pumping: ____/____/____
month day year

4. Septic Hauling Company Name and Contact Info:

5. Components and Volumes Pumped _____

<input type="checkbox"/> Cesspool(s)	<input type="checkbox"/> Septic Tank	<input type="checkbox"/> Tight Tank	<input type="checkbox"/> Grease Trap	<input type="checkbox"/> Pump Chamber	<input type="checkbox"/> Other: _____
_____	_____	_____	_____	_____	_____
Gallons	Gallons	Gallons	Gallons	Gallons	Gallons

6. Condition of Covers and Safety Grates: Identify every cover observed. For each cover, answer all questions.

COVER 1: LOCATION: Septic Inlet / Septic Middle / Septic Outlet / Cesspool / Pump / Treatment Tank / Leach Pit / _____
Other

COVER MATERIAL: Concrete / Cast Iron / Plastic or Fiberglass / Stone / _____
Other

COVER WEIGHT: Light Duty / Medium Duty / Heavy Duty / _____
Other

STYLE: Non-bolted / Detachable bolts / Non-detachable bolts / Entire cover twists into place / _____
Other

For LIGHT DUTY covers w/ detachable bolts: Pumper must supply and secure all bolt-holes. Are all bolt-holes secure? ___Yes ___ No
For LIGHT DUTY covers not in compliance with Sec. 4.2(b) Pumper must supply and install SAFETY GRATE if one can be installed
without modification to riser. SAFETY GRATE: ___Yes ___ No If NO, why not?

.....

COVER 2: LOCATION: Septic Inlet / Septic Middle / Septic Outlet / Cesspool / Pump / Treatment Tank / Leach Pit / _____
Other

COVER MATERIAL: Concrete / Cast Iron / Plastic or Fiberglass / Stone / _____
Other

COVER WEIGHT: Light Duty / Medium Duty / Heavy Duty / _____
Other

STYLE: Non-bolted / Detachable bolts / Non-detachable bolts / Entire cover twists into place / _____
Other

For LIGHT DUTY covers w/ detachable bolts: Pumper must supply and secure all bolt-holes. Are all bolt-holes secure? ___Yes ___ No
For LIGHT DUTY covers not in compliance with Sec. 4.2(b) Pumper must supply and install SAFETY GRATE if one can be installed
without modification to riser. SAFETY GRATE: ___Yes ___ No If NO, why not?

.....

COVER 3: LOCATION: Septic Inlet / Septic Middle / Septic Outlet / Cesspool / Pump / Treatment Tank / Leach Pit / _____
Other

COVER MATERIAL: Concrete / Cast Iron / Plastic or Fiberglass / Stone / _____
Other

COVER WEIGHT: Light Duty / Medium Duty / Heavy Duty / _____
Other

STYLE: Non-bolted / Detachable bolts / Non-detachable bolts / Entire cover twists into place / _____
Other

For LIGHT DUTY covers w/ detachable bolts: Pumper must supply and secure all bolt-holes. Are all bolt-holes secure? ___Yes ___ No
For LIGHT DUTY covers not in compliance with Sec. 4.2(b) Pumper must supply and install SAFETY GRATE if one can be installed
without modification to riser. SAFETY GRATE: ___Yes ___ No If NO, why not?

.....

7. Effluent Filter(s) Present: ___Yes ___ No If yes, cleaned? ___Yes ___ No
(Note: Effluent filters should be cleaned AFTER pumping septic tank, not before.)

8. Note any Safety or Health Issues: _____

9. Condition of the System: _____ 10. Location where contents disposed: _____

11. System Pumped By _____ Signature: _____
Hauler / Driver's Name

Sections of Hamilton Board of Health Regulation: *Septic System Access Covers*, adopted April 2018

3. Definitions

Light Duty Cover – 18” diameter cover weighs less than 25 pounds; 24” diameter covers weighs less than 50 pounds.

Medium Duty Cover – 18” diameter cover weighs 25 pounds to 35 pounds; 24” diameter cover weighs 50 pounds to 70 pounds.

Heavy Duty Cover – 18” cover weighs more than 35 pounds; 24” diameter cover weighs more than 70 lbs.

4. Access Covers

4.1. In order to decrease the risk of a person or animal falling into a septic tank (or similarly dangerous septic component, e.g. pump chamber, holding tank, cesspool, treatment tank, leach pit, dry well) the following regulation is enacted. Light-duty access covers that require bolts or screws (or similar) to secure the cover from unauthorized access, and where the bolts/screws are detachable, are generally not allowed, unless they meet the exceptions described below. The rationale for this regulation is that bolts/screws can be misplaced leaving the cover unsecured.

4.2. Access covers are in compliance with this regulation when they are:

- a) Medium (or Heavy) Duty (typically made of concrete, stone, or cast iron).
- b) Light Duty, under the following conditions:

- i) Light Duty covers that are secured to the frame by means of bolts, screws or similar that cannot be detached from the cover. Cam-Lock or Roto-Lock are acceptable examples of non-detachable means of securing covers.
- ii) Light Duty covers that are secure *without* the use of bolts are allowed. For example, plastic covers in which the entire cover turns and screws into the tank or riser (e.g. certain poly tanks) are allowed.
- iii) Light Duty covers with *detachable* bolts are allowed only if:
 - a) the tank is filled with sand, stone, or other filter media that are capable of supporting a 250 lbs point load, or
 - b) the passage into the tank is blocked by equipment or other structures that would keep a small child from falling into the tank, and is capable of supporting a 250 lbs point load.

4.4. Pump Out

- a) At the time of a septic pump-out, the Pumper shall note the status of all covers observed on a “Septic System Pumping Record” form provided by the Board of Health, and submit this form to the Board of Health within 14 days of pumping.
- b) Any safety issues must be noted by the Pumper on the “Septic System Pumping Record” and a copy of which shall be given by the Pumper to the owner.
- c) Covers not in conformance with 4.2 must have:
 - i) a safety grate in place. If there is no safety grate, the Pumper must supply and put one in place (when one can be put in place safely and without making alterations to the riser).
 - ii) all bolts securely fastened. If additional bolts are needed, the Pumper shall supply and attach them.